

[Companies](#) | [Log In](#) | [Contact Us](#)

[Home](#) | [Products](#) | [Solutions](#) | [References](#) | [Download](#) | [Address](#)

Item Table  
Product Table  
Documentation  
Accessories  
Images  
Print

PDF

Architectural  
Downlight  
Downlight  
Halogen  
Spotlight  
Commercial  
Industry

- Ceiling recessed
- Ceiling surface
- Suspended - pendants
- Hazardous Area
- Outdoor
- Emergency
- Heating Products

industry ceiling surface

## GPV2

- **Recyclable glass reinforced polyester luminaire housing**
- **Stainless steel clips**
- **IP67**

2 and 1 lamp GPV2.

**Specifications**  
Luminaire housing in grey recyclable glass reinforced polyester. Polycarbonate diffuser. White painted geartray. Diffuser clips in stainless steel. D-marked with electronic ballast (HF). Some variants can be delivered with emergency lighting systems.

**Light source**  
1- and 2-tube T5 28 - 35 - 49W. 1-tube T8 18 - 36 - 58W. 2-tube T8 36 - 58W.

**Ballast**  
Compensated conventional ballast (F), electronic ballast (HF), analogue dimming (HFDa), digital dimming (HFDd) or DALI.

**Mounting**  
Ceiling or wall, on luminaire tracks or on horizontal wire.

**Optics**  
Reflector in anodised aluminium on request.

**Connection**  
5-way 2,5 mm<sup>2</sup> terminal block. 1 x M20 cable gland in each end (cabel Ø7 - 14 mm).  
5 x 2,5 mm<sup>2</sup> through wiring.

**IP67, Ta=25°C**
**(HF)**

Copyright © 1947-2011 Glamox Distributors. All rights reserved.