



NORTE

Low-Bay Luminaire



Norte 1250 G96 HI **GRID**



Norte 1250 G96 HI **FRAME**

- Type:** Luminaire for high mounting applications for metal halide lamps. High performance, ideal for high mounting applications.
- Specification:** White painted steel body. Parabolic reflector in symmetrical faceted aluminum with clear glass cover. Luminaire is plastic-wrapped and packed separately.
- Installation:** Suitable for surface mounting on ceilings.
- Application:** For use in factories, warehouses, garages, halls and many others commercial applications.

Type	Description	Lamp (W) and holder	Overall dimensions, mm	Weight, kg	Total wattage, W
Norte 1150 G95 HI	HI	1x150 (E27)	365x490x175	7,5	170
Norte 1250 G96 HI	HI	1x250 (E40)	365x490x175	7,9	280
Norte 1400 G97 HI	HI	1x400 (E40)	365x490x175	8,4	440
Norte 1150 G98 HS	HS	1x150 (E40)	365x490x175	7,5	170
Norte 1250 G96 HS	HS	1x250 (E40)	365x490x175	7,9	280
Norte 1400 G97 HS	HS	1x400 (E40)	365x490x175	8,4	440

Options available on request:

- | | | | |
|------|---------------------------------|-------|-------------------------------|
| TP | - Built-in thermal protector | AS | - Asymmetric reflector |
| HS | - For high pressure sodium lamp | FRAME | - Frame for recessed mounting |
| GRID | - Protection grid | IP65 | - IP65 version |



NORTE LED1X15100 B635 T750

Type	Description	Overall dimensions, mm	Luminous flux, lm	Color temperature, K	Color rendering, Ra	Total wattage, W	Weight, kg
Norte LED1x10100 B633 T750 L45	Lens 45°	365x490x175	10100	5000	70	88	8,5
Norte LED1x12600 B634 T750 L45	Lens 45°	365x490x175	12600	5000	70	110	8,5
Norte LED1x15100 B635 T750 L45	Lens 45°	365x490x175	15100	5000	70	132	8,5
Norte LED1x10100 B633 T750 L60	Lens 60°	365x490x175	10100	5000	70	88	8,5
Norte LED1x12600 B634 T750 L60	Lens 60°	365x490x175	12600	5000	70	110	8,5
Norte LED1x15100 B635 T750 L60	Lens 60°	365x490x175	15100	5000	70	132	8,5
Norte LED1x10100 B633 T750 L60x120	Lens 60x120°	365x490x175	10100	5000	70	88	8,5
Norte LED1x12600 B634 T750 L60x120	Lens 60x120°	365x490x175	12600	5000	70	110	8,5
Norte LED1x15100 B635 T750 L60x120	Lens 60x120°	365x490x175	15100	5000	70	132	8,5

Options available on request:

TP – Built-in thermal protector
 DIM – Dimmable ballast
 SWITCHDIM – Switch DIM ballast
 DALI – DALI ballast
 HS – For high pressure sodium lamp
 GRID – Protection grid
 FRAME – Frame for recessed mounting
 IP65 – IP65 version

AS – Asymmetric reflector
 T830 – Color temperature 3000K
 T840 – Color temperature 4000K
 T850 – Color temperature 5000K
 L45 – Lens 45°
 L60 – Lens 60°
 L60x120 – Lens 60x120°

NORTE 1400 G97 HI

